

NEMA Type 1, 2, 4 & 13
UL ENCLOSURE 1, 2, 4 & 13
CSA ENCLOSURE 1, 2, 4 & 13
EN 60529 Degree of Protection IP56

Drip tight • Dust tight • Watertight • Oil tight
MEDIUM DUTY COMPACT DESIGN



Materials of Construction:

- Cast aluminum body and treadle with steel base plate and nonskid base pad
- Single 3/4"-14 N.P.T. threaded conduit entry is standard

Features & Benefits:

- All models single stage momentary contact
- 2 holes provided for rigid mounting to floor or equipment

Options:

- Special threaded conduit entry available to the O.E.M. on special order (Dual / Metric)
- Single/Dual 1/2"-14 NPT threaded conduit entry
- Metric threaded conduit entry

| No Shield | |
|--|----------------------------|
| Size (HxWxD): | 2.25 In. x 3.50 x 6.20 In. |
| Weight: | 1.50 lbs. |
| Shielded | |
| Size (HxWxD): | 5.19 In. x 5.90 x 7.27 In. |
| Weight: | 2.75 lbs. |
| For Dimension Drawings visit www.linemaster.com and click on Line Drawings located under the Guides & Literature Tab | |

| ⚠ WARNING SEE PRODUCT WARNING ON PAGE 103 | | | | | | |
|---|-------------------------------|----------------|----------------------|---------|------|--|
| SPECIFICATIONS (Special variations are available to the O.E.M. on special order on the models listed below) | | | | | | |
| AGENCY APPROVALS | EN 60529 Degree of Protection | CATALOG NUMBER | DESCRIPTION | CIRCUIT | FORM | ELECTRICAL RATINGS |
| | IP56 | 78SN1 | Momentary | SPDT | C | 20 A 125-250 VAC 1 H.P. 125-250 VAC Heavy Pilot Duty 250 VAC Max. |
| | IP56 | 78SN2 | Momentary | DPDT | C | |
| | IP56 | 78SH1 | Momentary / Shielded | SPDT | C | |
| | IP56 | 78SH2 | Momentary / Shielded | DPDT | C | |