

## EN 60529 Degree of Protection IP68 and IP20

**Drip tight • Dust tight • Watertight • Rust Proof • Corrosion Resistant**  
**SMALL LIGHTWEIGHT LOW PROFILE DESIGN**

### Materials of Construction:

- Cover & Base formed from Light Gray (PMS 427C) ABS Polymeric Material
- Non-glare finish
- Silver Alloy contacts
- SPDT, DPDT, Two-Stage, Momentary Operation
- Integrated adjustable strain relief clamp accommodates cord sizes from .250" Dia. to .400" Dia

### Features & Benefits:

- Maximum versatility, total performance in a small package
- Rustproof and corrosion Resistant
- Mounting holes provided for rigid mounting to floor and or equipment
- Non-Skid Feet
- Raised Dimples on treadle for positive traction during operation
- 10 A 125-250 VAC rating
- Designed to meet UL, CSA & CE requirements

### Options:

- Custom colors and color matching available with quantity orders
- Fully submersible in water (IP68 Only)
- Twin & Triple models available
- Accessory base units available for configurations using multiple switches
- Heavy gauge steel guard available (See "Accessories - Guards" on pages 94 & 95 for details)
- Custom connectivity options including Universal Serial Bus (USB)
- Custom cabling available
- 3 A 125-250 VAC & 5 A 125-250 VAC ratings available



Size (HxWxD):	1.05 x 2.50 x 3.48 In.
Weight:	4 oz.

For Dimension Drawings visit [www.linemaster.com](http://www.linemaster.com) and click on Line Drawings located under the Guides & Literature Tab

<b>⚠ WARNING SEE PRODUCT WARNING ON PAGE 103</b>						
This device is of an application specific design. Please Contact LINEMASTER® for additional Information: 1-860-974-1000						
AGENCY APPROVALS	EN 60529 Degree of Protection	CATALOG NUMBER	DESCRIPTION	CIRCUIT	FORM	ELECTRICAL RATINGS
	IP10	SL1-S	Single Pedal/Momentary	SPDT	C	10 A 125-250 VAC
	IP10	SL2-S	Single Pedal/Momentary	SPDT - 2 Stage	C	
	IP10	SL4-S	Single Pedal/Momentary	DPDT	C	
	IP68	SL1-SWBNO210 <sup>1</sup>	Single Pedal/Momentary	SPDT	C	5 A 125-250 VAC
	IP68	SL2-SWBNO410 <sup>2</sup>	Single Pedal/Momentary	SPDT - 2 Stage	C	
	IP68	SL4-SWANO410 <sup>2</sup>	Single Pedal/Momentary	DPDT	C	3 A 125 VAC 2 A 250 VAC
	IP68	SL4-SWBNO310 <sup>3</sup>	Single Pedal/Momentary	DPDT	C	5 A 125-250 VAC
	IP68	SL4-SWBNO410 <sup>2</sup>	Single Pedal/Momentary	DPDT	C	

<sup>1</sup> Supplied with 10 ft., 2 conductor, 18 awg cord    <sup>2</sup> Supplied with 10 ft., 4 conductor, 18 awg cord    <sup>3</sup> Supplied with 10 ft., 3 conductor, 18 awg cord