



LED Permanent Beacon



LED Traffic Light Combination with mounting bracket (accessory)



Clear lenses ensure effective signalling even in direct sunlight

**i TECHNICAL SPECIFICATIONS/ORDER SPECIFICATIONS:**

<b>Dimensions (Ø x Height):</b>	150 mm x 154 mm	
<b>Housing:</b>	PC/ABS-Blend, grey	
<b>Lens:</b>	PC, transparent	
<b>Fixing:</b>	Base mounting, bracket mounting (accessory), tube mounting (accessory)	
<b>Cable entry:</b>	From top or bottom with cable gland M20 x 1.5 mm or from the back with rubber grommet Ø 6-12 mm, included in assembly.	
<b>Colours:</b>	Red, green, yellow	
<b>Connection:</b>	CAGE CLAMP® 0.5 - 1.5 mm <sup>2</sup>	
<b>Installation position:</b>	As required	
<b>Life duration:</b>	Up to 50,000 hrs	

<b>LED Beacon/LED Traffic Light</b>		
<b>Voltage:</b>	12-24 V DC	115-230 V AC
<b>Current consumption:</b>	< 200 mA	< 35 mA
red	<b>890 120 55</b>	<b>890 120 68</b>
green	<b>890 220 55</b>	<b>890 220 68</b>
yellow	<b>890 320 55</b>	<b>890 320 68</b>

<b>LED Permanent Light (RGY)</b>		
<b>Voltage:</b>	12-24 V DC	230 V AC
<b>Current consumption:</b>	< 220 mA	< 40 mA
RGY (red, green, yellow)	<b>890 480 55</b>	<b>890 480 68</b>

**ACCESSORIES:**

<b>FIXING BRACKET</b>	
Fixing bracket for one beacon	<b>975 890 33</b>
Fixing bracket for two beacons	<b>975 890 34</b>
Fixing bracket for three beacons	<b>975 890 35</b>
Fixing bracket for four beacons	<b>975 890 37</b>

Mounting material and connecting grommet included in assembly. Further information can be found on page 183.

<b>CONNECTING GROMMET</b>	
Connecting grommet for traffic light combinations	<b>975 890 25</b>

**! ADDITIONAL INFORMATION:**

Traffic light configurator at [www.werma.com](http://www.werma.com)

**TECHNICAL DIAGRAMS: see page 181**

Signalisation index	
LED Permanent Light	

