



LED Traffic Light (3 tier)



The direction of the optical signal can be individually adjusted



Clear lenses ensure effective signalling even in direct sunlight

**i TECHNICAL SPECIFICATIONS/ORDER SPECIFICATIONS:**

<b>Dimensions (Ø x Height):</b>	2 tier: 85 mm x 309 mm x 136 mm	
	3 tier: 85 mm x 394 mm x 136 mm	
<b>Housing:</b>	PC/ABS, grey	
<b>Lens:</b>	PC, transparent	
<b>Fixing:</b>	Wall mounting, tube mounting (accessory)	
<b>Cable entry:</b>	Cable diameter max. 13 mm	
<b>Connection:</b>	Screw terminal 0.5 - 1.5 mm <sup>2</sup>	
<b>Installation position:</b>	Vertical/hanging	
<b>Duty cycle:</b>	100 %	
<b>Life duration:</b>	Up to 50,000 hrs	
<b>Voltage:</b>	24 V DC	115-230 V AC
<b>Current consumption:</b>	60 mA (red/yellow)	30 mA per tier
	120 mA (green)	at 230 V/50 Hz
red/green	<b>894 160 55</b>	<b>894 160 68</b>
red/yellow/green	<b>894 180 55</b>	<b>894 180 68</b>

**ACCESSORIES:**

Fixing bracket underneath	<b>975 894 01</b>
---------------------------	-------------------

**TECHNICAL DIAGRAM:**

