

## EN 60529 Degree of Protection IP20 (IP68 Upon Request)

**Splash Resistant • Corrosion Resistant (Available)**

**LIGHT DUTY GENERAL PURPOSE DESIGN**

### Materials of Construction:

- Steel Housing is painted black
- Ribbed rubber foot pad for traction
- Steel fasteners
- Non-skid base pad for traction on various surfaces
- Internal plastic strain relief connector

### Features & Benefits:

- Proven Reliability
- 2 holes provided for rigid mounting to floor or equipment
- The low profile and light pressure required to operate reduces operator fatigue.
- Front Hinge position for ease of actuation.

### Options:

- Heavy gauge steel guard available
- Cabled variations available
- Multipedal options available on special order.



Size (HxWxD):	1.18 x 2.89 x 3.60 In.
Weight:	7 oz. / 1 lb. Corded

*For Dimension Drawings visit [www.linemaster.com](http://www.linemaster.com) and click on Line Drawings located under the Guides & Literature Tab*

### **⚠️ WARNING SEE PRODUCT WARNING ON PAGE 103**

SPECIFICATIONS (Special variations are available to the O.E.M. on special order on the models listed below)

AGENCY APPROVALS	EN 60529 Degree of Protection	CATALOG NUMBER	DESCRIPTION	CIRCUIT	FORM	ELECTRICAL RATINGS
	IP20	T-91-SFZ	Single / Momentary	SPDT	C	15 A 125-250 VAC 1/2 H.P. 125-250 VAC
	IP20	T-91-SC3FZ <sup>1</sup>	Single / Momentary	SPDT Wired N.O.	A	10 A 125 VAC 1/2 H.P. 125 VAC
	IP20	T-91-SC36FZ <sup>2</sup>	Single / Momentary	SPDT Wired N.O.	A	10 A 125 VAC 1/2 H.P. 125 VAC

<sup>1</sup> Supplied with 6 ft. 18/3 cord with 3 prong series plug. Green lead grounded.

<sup>2</sup> Supplied with 6 ft. 18/3 cord without plug. Green lead grounded.