

Treadlite II - Stainless Steel



EN 60529 Degree of Protection IP68
NEMA Type 1, 4X, 6, & 6P IP68
UL Enclosure 1, 4X, 6, & 6P

Drip tight • Dust tight • Watertight • Corrosion Resistant (Available)
COMPACT VERSATILE LOW PROFILE DESIGN

Materials of Construction:

- Stainless Steel housing with brushed finish

Features & Benefits:

- Nonskid base pad and foot treadle pad
- The low profile and light pressure required to operate reduces operator fatigue

Options:

- Stainless Steel Full Guard Available
 (See “Accessories - Guards” on page 95 for details)



Size (HxWxD):	.85 x 2.63 x 3.50 In.
Weight:	8.00 oz.

For Dimension Drawings visit www.linemaster.com and click on Line Drawings located under the Guides & Literature Tab

⚠ WARNING SEE PRODUCT WARNING ON PAGE 103						
SPECIFICATIONS (Special variations are available to the O.E.M. on special order on the models listed below)						
AGENCY APPROVALS	EN 60529 Degree of Protection	CATALOG NUMBER	DESCRIPTION	CIRCUIT	FORM	ELECTRICAL RATINGS
cUL US	IP68	T-91-SWANOS ¹	Momentary	SPST-N.O.	A	3 A 125-250 VAC
cUL US	IP68	T-91-SWANO3S ²	Momentary	SPST wired N.O.	A	3 A 125 VAC
cUL US	IP68	T-91-SWANO38S ³	Momentary	SPST wired N.O.	A	3 A 125-250 VAC

¹Supplied without cordset.
²Supplied with 8 ft. 18/3 cord and 3-prong series plug, green lead grounded.
³Supplied with 8 ft. 18/3 cord without plug, green lead grounded.